

Technical data

(for standard equipment)



Machine

Minimal length, overall	~4,75	m
Minimal width, overall	~0,78	m
Minimal height, travel position	~1,99	m
Total weight	~1400	kg
Live load in traveling position	~4,27	kN/m ²
Live load in work position	~1,75	kN/m ²

Boom system

Max. working height with 200 kg	~12,75	m
Max. working height with 400 kg	-	m
Side reach with 80 kg	~6,05	m
Side reach with 200 kg	~6,05	m
Side reach with 400 kg	-	m
Max. basket load limit	200	kg
Basket rotation	-	°
Basket dimension (LxWxH)	1,42 x 0,7 x 1,1	m
Movable jib	-	°
Carriage rotation	~360	°
Carriage rotation, one side narrow	-	°
Carriage rotation, both side narrow	-	°

Outrigger

Width, outriggers deployed max./min.	~3	~2,86	m
One side narrow, out. depl. max./min.	-	-	m
Both side narrow, out. depl. max./min.	-	-	m
Outrigger foot (LxW)	Ø=0,2		m
To be jacked up to ground slope of	~10	~18	° %
Max. ground clearance	~40		cm

Track system

Height and width track adjustment	-	-	cm
Gradeability	~14,5	~26	° %
Slope angle	~14,5	~26	° %
Chain (LxW)	~118 x 18		cm
Travel speed	~1,0		km/h
Max. ground clearance	~20		cm

Engine

Manufacturer	-		
Horse Power	-	-	kw PS
Fuel tank capacity	-		
Manufacturer electric motor	EMG-EBS 90 L X 4-50Hz		
230 V	12,9	2,2	A kw
400 V	-	-	A kw

Version (date):

22.10.2009

We reserve the right to make technical alterations!

